

Amendments to the Claims:

Please amend Claims 30 and 44 to read, as follows.

Claims 1 through 29. **(Canceled)**

30. **(Currently Amended)** A cartridge detachably mountable to an image forming apparatus, said cartridge comprising:

a first container for containing a developer to be supplied into the image forming apparatus;

a developer discharge opening provided at one longitudinal end side of said first ~~container; container,~~

a drive input portion, provided at the one longitudinal end side, for receiving a driving force for rotating said first container from the image forming apparatus when the developer is fed toward said discharge opening; and

a second container for accommodating a developer collected from the image forming apparatus,

wherein said first container is rotatably supported, at the other longitudinal end side thereof, by said second container, which is unrotatably engageable with the image forming apparatus.

31. **(Previously Presented)** A cartridge according to Claim 30, wherein when said first container rotates, a substantial rotational center of said first container is supported by said second container.

32. **(Canceled)**

33. **(Canceled)**

34. **(Previously Presented)** A cartridge according to Claim 30 or 31, wherein said first container includes a projection, which is projected toward said first container, and which is supported by said second container.

35. **(Previously Presented)** A cartridge according to Claim 34, wherein said projection includes a limiting portion for limiting movement of said first container in a longitudinal direction of said first container.

36. **(Previously Presented)** A cartridge according to Claim 35, wherein said limiting portion includes a snap-fit structure for snap-fitting with said second container.

37. **(Previously Presented)** A cartridge according to Claim 34, wherein said projection is hollow to accommodate the developer.

38. **(Previously Presented)** A cartridge according to Claim 30, further comprising a vibrating portion for vibrating said first container and said second container with rotation of said first container.

39. **(Previously Presented)** A cartridge according to Claim 30, wherein said first container has an opening, at the other longitudinal end side of said first container, for permitting said first container to be filled with a developer, and wherein said second container is provided so as to cover said opening.

40. **(Previously Presented)** A cartridge according to Claim 39, further comprising a cap for capping said opening, wherein said second container is effective to prevent said cap from disengaging.

41. **(Previously Presented)** A cartridge according to Claim 30, wherein the developer to be supplied and the collected developer contain toner and carrier particles.

42. **(Previously Presented)** A cartridge according to Claim 30, wherein said second container is provided with a receiving opening for receiving the collected developer, and wherein the receiving opening is stationary when the developer is collected.

43. **(Previously Presented)** A cartridge detachably mountable to an image forming apparatus, said cartridge comprising:

a first container for containing a developer to be supplied into the image forming apparatus;

a filling opening, provided at one longitudinal end side of said first container, for permitting said first container to be filled with the developer; and

a second container for accommodating the developer collected from the image forming apparatus,

wherein said second container is disposed so as to cover said filling opening.

44. **(Currently Amended)** A cartridge according to Claim 43 ~~[[42]]~~, further comprising a cap for capping said filling opening, wherein said second container is effective to prevent said cap from disengaging.